

EC 300 F

Engine	4-stroke Single-cylinder, liquid-cooled
Displacement	290.0 cc
Cylinder head	5 valves with double overhead camshaft
Bore and stroke	83.0 x 53.6 mm
Start	Electric and kick
Ignition	Electronic
Gearbox	5-speed with foot control
Clutch	Multidisc in oil bath
Carburettor	Keihin fcr-mx37
Muffler	Reverse
Bodywork	Unbreakable plastic
Handlebar	GasGas Double Force
Frame	Perimeter frame in chrome-molybdenum
Subframe	Tubular aluminum alloy
Swingarm	Aluminium, progressive system with tie rods
Front forks	Marzocchi shiver inverted ø48 mm, closed cartridge
Fork travel	305 mm
Fork adjuster	Spring preload, rebound and compression
Shock absorber	Reiger Mono shock, Special settings
Shock absorber adjuster	Spring preload, rebound and compression high/low speed
Rear wheel travel	298 mm
Wheel rims	Excel Aluminium spoke rim
Tyres:	Front: 1.6 x 21 - 90/90 - 21 pirelli six days extreme
Tyres:	Rear: 2.15 x 18 - 140/80 - 18 pirelli six days extreme
Front brake	Galfer disc "wave" 260 mm, 2 pistons nissin calliper
Rear brake	Galfer disc "wave" 220 mm, 1 piston nissin calliper
Fuel	8,2 l (high octane)
Dry weight	108 kg
Dimensions	Length x width x height: 2200 x 830 x 1260 mm
Wheelbase	1.490 mm
Seat height	950 mm